



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2000035570 A**(43) Date of publication of application: **02.02.00**

(51) Int. Cl.

G02F 1/1335(21) Application number: **10201392**(22) Date of filing: **16.07.98**(71) Applicant: **SHARP CORP**(72) Inventor: **KUBO MASUMI
NARUTAKI YOZO
FUJIOKA SHIYUGO**(54) **LIQUID CRYSTAL DISPLAY DEVICE**be perpendicular to that of the $\lambda/2$ -wave plate 11.

(57) Abstract:

COPYRIGHT: (C)2000,JPO

PROBLEM TO BE SOLVED: To improve coloring in a reflection mode of dark display by eliminating the variation of polarization in the light wavelength band, and approximately circular-polarizing the light in the reflection mode.

SOLUTION: A $\lambda/4$ -wave plate 7 is arranged on the opposite plane of the side where a counter electrode 4 of a substrate 2 is formed, and further, a $\lambda/4$ -wave plate 10 is arranged on the opposite plane of the side where a reflecting electrode 3 and a transparent electrode 8 of a substrate 1 are formed, and the lagging axis, of the $\lambda/4$ -wave plate 10 is set so as to be perpendicular to that of the $\lambda/4$ -wave plate 7. A $\lambda/2$ -wave plate 11 is arranged on the other side of the substrate 2 of the $\lambda/4$ board 7 and a $\lambda/2$ -wave plate 12 is arranged on the other side of the substrate 1 of the $\lambda/4$ -wave plate 10, respectively, and the lagging axis of the $\lambda/2$ -wave plate 11 is set to be 60 degrees tilted against that of $\lambda/4$ -wave plate 7; the lagging axis of the $\lambda/2$ -wave plate 12 is set to be 60 degrees tilted against that of $\lambda/4$ -wave plate 10; and the lagging axis of the $\lambda/2$ -wave plate 12 is set to

6. 偏光板	
11. $\lambda/2$ 板	
7. $\lambda/4$ 板	
2. 基板	
4. 対向電極	
5. LC層 (垂直配向)	
3. 反射電極	8. 透明電極
1. 基板	
10. $\lambda/4$ 板	
12. $\lambda/2$ 板	
9. 偏光板	